

# PROMASTOP®-IM Grille

## Fire Stopping Ventilation Grille

TECHNICAL DATA SHEET



### QUALITY ASSURANCE

Promat products are manufactured to stringent quality control systems to assure that our customers receive materials made to the highest standards.

Operating to these standards means that all activities, which have a bearing upon quality, are set out in written procedures.

Systematic and thorough checks are made on all materials and their usage. Test equipment is subjected to regular checks and is referred back to national standards.

The information given in this data sheet is based on actual tests and is believed to be typical of the product. No guarantee of results is implied however, since conditions of use are beyond our control.

### SAFETY INSTRUCTION

- Keep out of reach of children
- Avoid contact with food and beverages
- Please refer to the safety data sheet for additional advice

### GENERAL DESCRIPTION

PROMASTOP®-IM Grille is an intumescent sealing system for ventilation openings. The expansion of the grill starts at approx. 190 °C and seals the opening against spread of smoke and fire.

### FIELD OF APPLICATION

PROMASTOP®-IM Grille is used as ventilation grill in walls.



### SYSTEM ADVANTAGE / CUSTOMER BENEFIT

- Module system
- Slim design
- Resistant to atmospheric influences (light, heat, frost, UV radiation, humidity)

### STORAGE REQUIREMENTS

- Store in cool and dry conditions

### GENERAL TECHNICAL PROPERTIES

<b>Colour</b>	dark grey
<b>Consistency</b>	solid
<b>Dimension (HxWxD)</b>	100 x 100 x 80 mm
<b>Weight</b>	approx. 300 g
<b>Expansion temperature</b>	approx. 190 °C
<b>Open cross-sectional area</b>	approx. 70 %

### PACKAGING

- 52 pcs./box  
Minimum order quantity: 624 pcs. (12 boxes)